



Shell  
**Naturelle**

# Balancing sustainability and performance

**Shell Naturelle lubricants protect your equipment and the environment.**





They go beyond being “environmentally acceptable” to reducing emissions, thanks to renewable and sustainable biobased raw materials. Shell Naturelle offers a sustainable choice without compromising on performance.

# Shell Naturelle

## Balancing sustainability and performance

Reducing the environmental impact of critical operations does not mean that you need to compromise on productivity or protection. Shell has a broad portfolio of marine products designed for a wide range of conditions and applications, including lubricants especially suited for environmentally sensitive areas and operations in or near water.

Talk to your Shell representative to find out which products and services are right for your business.

	Gear fluid	Stern tube fluid	Greases
<b>Product</b> 	Shell Naturelle S4 Gear Fluid	Shell Naturelle S4 Stern Tube Fluid	Shell Naturelle S2 Grease A600P 1.5
<b>Applications</b>	<ul style="list-style-type: none"> <li>Industrial gears, bearings in circulation and splash systems</li> <li>Marine propulsion drives, thrusters, controllable-pitch propellers and stern tubes</li> </ul>	<ul style="list-style-type: none"> <li>Stern tubes and controllable-pitch propellers</li> </ul>	<ul style="list-style-type: none"> <li>Wire ropes, cables, fairleads, and crane and davit wires</li> <li>Open gears and low-speed plain bearings (&lt; 500 rpm)</li> <li>Rudder stocks and trunk voids, propeller caps</li> <li>Dredging bucket wheels</li> </ul>
<b>Benefits</b> 	<ul style="list-style-type: none"> <li>Excellent load-carrying capacity and anti-scuffing performance</li> <li>Excellent water separation</li> <li>Wide temperature range</li> </ul>	<ul style="list-style-type: none"> <li>Designed to offer superior lubrication performance</li> <li>Non-emulsifying</li> <li>High viscosity index providing low-torque system startup and maintaining fluid film thickness at higher operating temperatures</li> </ul>	<ul style="list-style-type: none"> <li>Excellent adhesion and wash-off resistance</li> <li>Extreme pressure and antiwear</li> <li>Excellent corrosion protection</li> </ul>
<b>Technology</b>	Fully saturated ester	Fully saturated ester	Calcium complex
<b>ISO viscosity grades</b> 	68, 100, 150	100	600
<b>NLGI grade</b>			1.5
<b>Specifications and approvals*</b> 	US EPA VGP 2013 compliant; DIN 51517-3 CLP; EU Ecolabel on ISO 150 DE/027/290; Kongsberg: 68, 100, 150, KHI: 68, 100; Schottel: 100, 150; Brunvoll: 68, 100; Wärtsilä: 68, 100, 150	US EPA VGP compliant; SKF Marine; Wärtsilä Propulsion KEMEL; AEGIR-Marine; EU Ecolabel DE/027/290	US EPA VGP compliant



Find out more by visiting  
[www.shell.com/marine](http://www.shell.com/marine)

